



Heating Products



CALLSAVE 1850 211 485

Address: Unit 8, Block 18 Duleek business Park, Duleek, Co. Meath, Ireland
Email: info@citycool.ie Website: www.citycool.ie

Ref: CC 04/08

The Complete Range



Fan Heaters



FH901



HFH201



PFH305



PBHFI

- Built-in Ioniser
- 45W fan only mode for summer use

Fan Heaters

| Model | FH901 | HFH201 | PFH305 | PBHFI |
|--|---------------|---------------|----------------|--------------------------|
| Barcode | 5038973001460 | 5038973003617 | 5038973003433 | 5038973003587 |
| ITF 14 digit barcode (outer carton) | - | - | 05038973003488 | - |
| Features | | | | |
| Heat settings | 2 | 2 | 2 | 2 |
| Fan only option | ✓ | ✓ | ✓ | ✓ |
| LCD Display | - | - | - | - |
| Controls - Push button, rotary, rocker, slide, pull cord, electronic, Remote control | Rotary | Rotary | Rotary | Rotary |
| Adjustable thermostat | ✓ | ✓ | ✓ | ✓ |
| Frost protection setting | ✓ | ✓ | ✓ | - |
| Tip over safety cut-out | - | - | - | - |
| Overheat safety cut-out | ✓ | ✓ | ✓ | ✓ |
| Carry handle(s) | ✓ | - | ✓ | ✓ |
| Cord storage | - | - | - | ✓ |
| Power on indicator light | - | - | ✓ | - |
| Oscillating function | - | - | - | Oscillating front grille |
| Timer hrs | - | - | - | - |
| IPX4 - Splash proof | - | - | - | - |
| Wall mountable | - | - | - | - |
| Castors for easy mobility | - | - | - | - |
| Specification | | | | |
| Main body material | Plastic | Plastic | Plastic | Plastic |
| Power - Heat (kW) | 2 | 2 | 2 | 2.3/ Cool 45W |
| Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 |
| Frequency (Hz) | 50 | 50 | 50 | 50 |
| Protection class I or II | II | II | II | II |
| Plug Amp (A) | 13 | 13 | 13 | 13 |
| Net weight - product (kg) | 1 | 2 | 1 | 5 |
| Gross weight - retail box (kg) | 2 | 2.3 | 1.3 | 5.35 |
| Gross weight - outer carton (kg) | 13 | 15 | 9 | - |
| Product dimensions - (HxWxD cm) | 24x24x12 | 13x27.5x26.5 | 25x23x13 | 51.5x40x23.5 |
| Retail box dimensions - (HxWxD cm) | 25.5x25x12.5 | 27x26.5x13 | 26x23x13 | 54x43x21 |
| Outer carton dimensions - (HxWxD cm) | 52.5x40x27 | 56x41.5x27.5 | 53.5x41x24.5 | - |
| Number in outer carton | 6 | 6 | 6 | - |

All Prem-Air products are RoHS compliant and carry the WEEE Directive logo



Elite Range Ceramic & Fan Heaters



PECCB3200



PERCB3200



PEHDM180



PECF109



PERF109



PETF109



PECTL151



PERTL151



PETT151

| Model | Ceramic Heaters | | | Fan Heaters | | | | | | |
|--|-----------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|--|
| | PECCB3200 | PERCB3200 | PEHDM180 | PECF109 | PERF109 | PETF109 | PECTL151 | PERTL151 | PETT151 | |
| Barcode | 5038973003419 | 5038973003389 | 5038973003440 | 5038973003402 | 5038973003372 | 5038973004386 | 5038973003426 | 5038973003396 | 5038973004287 | |
| ITF 14 digit barcode (outer carton) | - | - | - | - | - | - | - | - | - | |
| Features | | | | | | | | | | |
| Heat settings | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | |
| Fan only option | - | - | ✓ | - | - | - | - | - | - | |
| LCD Display | - | - | - | - | - | - | - | - | - | |
| Controls - Push button, rotary, rocker, slide, pull cord, electronic, Remote control | Slide Switch | Slide Switch | Rotary | Rotary | Rotary | Rotary | Rotary | Rotary | Rotary | |
| Adjustable thermostat | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Frost protection setting | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Tip over safety cut-out | - | - | - | - | - | - | ✓ | ✓ | ✓ | |
| Overheat safety cut-out | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Carry handle(s) | - | - | ✓ | - | - | - | - | - | - | |
| Cord storage | - | - | - | - | - | - | - | - | - | |
| Power on indicator light | ✓ | ✓ | ✓ | - | - | - | - | - | - | |
| Oscillating function | - | - | - | - | - | - | - | - | - | |
| Timer hrs | - | - | - | - | - | - | - | - | - | |
| IPX4 - Splash proof | - | - | - | - | - | - | - | - | - | |
| Wall mountable | - | - | - | - | - | - | ✓ | ✓ | ✓ | |
| Castors for easy mobility | - | - | - | - | - | - | - | - | - | |
| Specification | | | | | | | | | | |
| Main body material | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | Plastic | |
| Power - Heat (kW) | 2 | 2 | 1.8 | 2 | 2 | 2 | 2 | 2 | 2 | |
| Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | |
| Frequency (Hz) | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | |
| Protection class I or II | II | II | II | II | II | II | II | II | II | |
| Plug Amp (A) | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | |
| Net weight - product (kg) | 1.60 | 1.60 | 1.80 | 1 | 1 | 1 | 1.80 | 1.80 | 1.80 | |
| Gross weight - retail box (kg) | 1.80 | 1.80 | 2.05 | 1.40 | 1.40 | 1.40 | 2.05 | 2.05 | 2.05 | |
| Gross weight - outer carton (kg) | 9 | 9 | 13 | 10 | 10 | 10 | 9 | 9 | 9 | |
| Product dimensions - (HxWxD cm) | 21.5x24.5x14 | 21.5x24.5x14 | 26x19.5x13 | 17x27x27 | 17x27x27 | 17x27x27 | 36x27x6 | 37x27x6 | 38x27x6 | |
| Retail box dimensions - (HxWxD cm) | 21.7x24.7x17 | 21.7x24.7x17 | | 16x29x28.5 | 16x29x28.5 | 16x29x28.5 | 37x28x9 | 38x28x9 | 39x28x9 | |
| Outer carton dimensions - (HxWxD cm) | 24.5x70x26 | 24.5x70x26 | 29x42.5x48.5 | 33x84x30 | 33x84x30 | 33x84x30 | 39.5x57x20.5 | 39.5x57x20.5 | 39.5x57x20.5 | |
| Number in outer carton | 4 | 4 | 6 | 6 | 6 | 6 | 4 | 4 | 4 | |

All Prem-I-Air products are RoHS compliant and carry the WEEE Directive logo

Please Note: Elite Heaters are available on special order. Small quantities may be available in general stock through the season.

Due to continuous research and development the specifications are subject to change without notice.



Ceramics, Convector & Panel Heaters



PCH0501



PTC2006RC

N10T24 Available on special order only.



N10



N10TURBO



N10T24



PPH5MA

PPH10MA

PPH15MA

PPH20MA

| Model | Ceramic Heaters | | Convector | | | Panel Heaters | | | |
|--|-----------------|--------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | PCH0501 | PTC2006RC | N10 | N10TURBO | N10T24 | PPH5MA | PPH10MA | PPH15MA | PPH20MA |
| Barcode | 5038973004393 | 5038973004232 | 5038973002504 | 5038973003105 | 5038973004287 | 5038973004324 | 5038973004331 | 5038973004348 | 5038973004355 |
| ITF 14 digit barcode (outer carton) | - | - | - | - | - | - | - | - | - |
| Features | | | | | | | | | |
| Heat settings | 2 | 2 | 3 | 3 | 3 | 1 | 1 | 1 | 1 |
| Fan only option | ✓ | ✓ | - | Turbo Fan | Turbo Fan | - | - | - | - |
| LCD Display | - | ✓ | - | - | - | - | - | - | - |
| Controls - Push button, rotary, rocker, slide, pull cord, electronic, Remote control | Rotary | Electronic with Remote Control | Push Button | Push Button | Push Button | Rotary | Rotary | Rotary | Rotary |
| Adjustable thermostat | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Frost protection setting | - | - | - | - | - | ✓ | ✓ | ✓ | ✓ |
| Tip over safety cut-out | ✓ | ✓ | - | - | - | - | - | - | - |
| Overheat safety cut-out | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Carry handle(s) | ✓ | ✓ | ✓ | ✓ | ✓ | - | - | - | - |
| Cord storage | - | - | - | - | - | - | - | - | - |
| Power on indicator light | ✓ | ✓ | ✓ | ✓ | ✓ | - | - | - | - |
| Oscillating function | - | ✓ | - | - | - | - | - | - | - |
| Timer hrs | - | 8 | - | - | 24 | - | - | - | - |
| IPX4 - Splash proof | - | - | - | - | - | ✓ | ✓ | ✓ | ✓ |
| Wall mountable | - | - | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Castors for easy mobility | - | - | - | - | - | ✓ | ✓ | ✓ | ✓ |
| Specification | | | | | | | | | |
| Main body material | Plastic | Plastic | Metal/Plastic | Metal/Plastic | Metal/Plastic | Metal | Metal | Metal | Metal |
| Power - Heat (kW) | 1.8 | 2 | 2 | 2 | 2 | 0.5 | 1 | 1.5 | 2 |
| Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 |
| Frequency (Hz) | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 |
| Protection class I or II | II | II | I | I | I | I | I | I | I |
| Plug Amp (A) | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 |
| Net weight - product (kg) | 1.40 | 3.1 | 3.4 | 3.4 | 3.4 | 4 | 5 | 6.7 | 8.8 |
| Gross weight - retail box (kg) | 1.90 | 4.2 | 4.6 | 4.6 | 4.6 | 4.8 | 6 | 8.3 | 10.9 |
| Gross weight - outer carton (kg) | 12 | - | - | - | - | - | - | - | - |
| Product dimensions - (HxWxD cm) | 28x19x17 | 60x23x21 | 44x65.5x17.5 | 45x65.5x17.5 | 46x65.5x17.5 | 40x46x8 | 40x64x8 | 40x93x8 | 40x126x8 |
| Retail box dimensions - (HxWxD cm) | 28.5x19.5x17.5 | 62x25x22 | 45x69x14.5 | 46x69x14.5 | 47x69x14.5 | 45x50.5x10.5 | 45x68.5x10.5 | 45x97.5x10.5 | 45x131x10.5 |
| Outer carton dimensions - (HxWxD cm) | 29.5x60x35.5 | - | - | - | - | - | - | - | - |
| Number in outer carton | 6 | - | - | - | - | - | - | - | - |

All Prem-Air products are RoHS compliant and carry the WEEE Directive logo



Panel heaters are supplied with castors

Due to continuous research and development the specifications are subject to change without notice.



Halogens & Patios



PHH31120




PHH31125



PHH31180



PHH31185



BH-1000E



PHH0800



HQH-2000S



ZEUS



JD0110V & JD0240V



HQH-2000W

| Model | Halogen Heaters | | | | | | BIG RADS | | Patio Heaters | | |
|--|----------------------|-----------------------------|----------------------|-----------------------------|---------------|---------------|---------------|---------------|---------------|---------------|--|
| | PHH31120 | PHH31125 | PHH31180 | PHH31185 | BH-1000E | PHH0800 | JD0110V | JD0240V | Halogen | Halogen | Carbon Fibre |
| Barcode | 5038973003495 | 5038973003501 | 5038973003518 | 5038973003525 | 5038973002344 | 5038973003624 | 5038973003594 | 5038973002600 | 5038973003112 | 5038973003273 | 5038973004423 |
| ITF 14 digit barcode (outer carton) | - | - | - | - | - | - | - | - | - | - | - |
| Features | | | | | | | | | | | |
| Heat settings | 3 | 3 | 4 | 4 | 2 | 2 | 2 | 2 | 3 | 3 | 1 |
| Fan only option | - | - | - | - | - | - | - | - | - | - | - |
| LCD Display | - | - | - | - | - | - | - | - | - | - | - |
| Controls - Push button, rotary, rocker, slide, pull cord, electronic, Remote control | Push Button | Electronic & Remote Control | Push Button | Electronic & Remote Control | Rocker | Rotary | Rocker | Rocker | Pull Cord | Pull Cord | PIR sensor auto shut off light, heater after 4 mins & Remote Control |
| Adjustable thermostat | - | - | - | - | - | - | - | - | - | - | ✓ |
| Frost protection setting | - | - | - | - | - | - | - | - | - | - | - |
| Tip over safety cut-out | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | - | ✓ |
| Overheat safety cut-out | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Carry handle(s) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | - | - | ✓ |
| Cord storage | ✓ Includes plug park | ✓ Includes plug park | ✓ Includes plug park | ✓ Includes plug park | - | - | ✓ | ✓ | - | - | ✓ |
| Power on indicator light | - | - | - | - | - | - | ✓ | ✓ | - | - | - |
| Oscillating function | ✓ | ✓ | ✓ | ✓ | - | - | - | - | - | - | - |
| Timer hrs | - | 7.5 | - | 7.5 | - | - | - | - | - | - | 4 minute auto shut down light |
| IPX4 / IPX5 - Splash proof | - | - | - | - | - | - | - | - | ✓ IPX4 | ✓ IPX4 | ✓ IPX5 |
| Wall mountable | - | - | - | - | - | - | - | - | - | ✓ | - |
| Castors for easy mobility | - | - | - | - | - | - | ✓ | ✓ | - | - | ✓ Rear rollers |
| Remote Control | - | - | - | - | - | - | - | - | - | - | ✓ |
| Specification | | | | | | | | | | | |
| Main body material | Plastic/Metal | Plastic/Metal | Plastic/Metal | Plastic/Metal | Plastic | Plastic | Metal | Metal | Metal | Metal | Metal |
| Power - Heat (kW) | 1.2 | 1.2 | 1.8 | 1.8 | 1 | 0.800 | 2 | 3 | 2 | 2 | 2.7 |
| Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 110 | 220-240 | 220-240 | 220-240 | 220-240 |
| Frequency (Hz) | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 |
| Protection class I or II | I | I | I | I | I | I | I | I | I | I | I |
| Plug Amp (A) | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 |
| Net weight - product (kg) | 3 | 3 | 3.9 | 3.9 | 1.95 | 1 | 15.7 | 15.7 | 9.5 | 1.65 | 28.30 |
| Gross weight - retail box (kg) | 3.8 | 3.8 | 4.9 | 4.9 | 2.63 | 1.25 | 17.7 | 17.7 | 10.5 | 2.1 | 31 |
| Gross weight - outer carton (kg) | 12.4 | 12.4 | 15.7 | 15.7 | 17 | 9 | - | - | - | 9.4 | - |
| Product dimensions - (HxWxD cm) | 55x33x19 | 55x33x19 | 71x33x19 | 71x33x19 | 20x37x18 | 41x27x11 | 88.5x55x49 | 88.5x55x49 | 210x50x50 | 26x52.5x23 | 210x33x33 |
| Retail box dimensions - (HxWxD cm) | 58x35x17 | 58x35x17 | 71x33x19 | 71x33x19 | 23x40x20 | 41x27x11 | 90x55x26 | 90x55x26 | 53x53x23 | 26x52.5x23 | 206x33x32 |
| Outer carton dimensions - (HxWxD cm) | 59x52x36 | 59x52x36 | 72x58x34 | 72x58x34 | 62x46x41 | 43x56x34.5 | - | - | - | 53.5x53.5x47 | - |
| Number in outer carton | 3 | 3 | 3 | 3 | 6 | 6 | - | - | - | 4 | - |

All Premier-Air products are RoHS compliant and carry the WEEE Directive logo

Due to continuous research and development the specifications are subject to change without notice.

• Available in 110V and 240V

• Includes weatherproof cover



Oil Filled Radiators



C307



C309



C3011T



PORCYPE-7

Oil Filled Radiators

| Model | C307 | C309 | C3011T | PORCYPE-7 |
|--|-----------------|-----------------|-----------------|-----------------|
| Barcode | 5038973002511 | 5038973002528 | 5038973002535 | 5038973003044 |
| ITF 14 digit barcode (outer carton) | - | - | - | - |
| Features | | | | |
| Heat settings | 3 | 3 | 3 | 1 |
| Fan only option | - | - | - | - |
| LCD Display | - | - | - | - |
| Controls - Push button, rotary, rocker, slide, pull cord, electronic, Remote control | Rocker & Rotary | Rocker & Rotary | Rocker & Rotary | Rocker & Rotary |
| Adjustable thermostat | ✓ | ✓ | ✓ | ✓ |
| Frost protection setting | ✓ | ✓ | ✓ | ✓ |
| Tip over safety cut-out | ✓ | ✓ | ✓ | ✓ |
| Overheat safety cut-out | ✓ | ✓ | ✓ | ✓ |
| Carry handle(s) | ✓ | ✓ | ✓ | ✓ |
| Cord storage | ✓ | ✓ | ✓ | - |
| Power on indicator light | ✓ | ✓ | ✓ | ✓ |
| Oscillating function | - | - | - | - |
| Timer hrs | - | - | 24 | - |
| IPX4 - Splash proof | - | - | - | - |
| Wall mountable | - | - | - | - |
| Castors for easy mobility | ✓ | ✓ | ✓ | - |
| Remote Control | - | - | - | - |
| Specification | | | | |
| Main body material | Metal | Metal | Metal | Metal |
| Power - Heat (kW) | 1.5 | 2 | 2.5 | 0.700 |
| Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 |
| Frequency (Hz) | 50 | 50 | 50 | 50 |
| Protection class I or II | I | I | I | I |
| Plug Amp (A) | 13 | 13 | 13 | 13 |
| Net weight - product (kg) | 11 | 13.2 | 15.4 | 4.8 |
| Gross weight - retail box (kg) | 12.2 | 14.6 | 17 | 5.4 |
| Gross weight - outer carton (kg) | - | - | - | 24 |
| Product dimensions - (HxWxD cm) | 65x37x23 | 65x45x25 | 65x52x25 | 42x35x12 |
| Retail box dimensions - (HxWxD cm) | 67x17.5x40 | 65.5x17x48 | 66x54x16 | 42x35x12 |
| Outer carton dimensions - (HxWxD cm) | - | - | - | 43.5x46x37 |
| Number in outer carton | - | - | - | 4 |
| All Premier-Air products are RoHS compliant and carry the WEEE Directive logo | | | | |

Due to continuous research and development the specifications are subject to change without notice.